



Item Description

- | Item | Description |
|------|-------------|
| 1 | O-ring |
| 2 | Lower body |
| 3 | Seal - S3 |
| 4 | Seal - S2 |
| 5 | Seal - S1 |
| 6 | Cap |

Technical Data For Non-Armor Cable Type

Equipment Marking	Ex II 2GD Ex d IIC Gb / Ex e IIC Gb (Flameproof Ex-d and Increased safety Ex-e)
Suitable For Used In	Zone 1, Zone 2, Zone 21, Zone 22 for Gas groups IIC / Dust group IIIC (Gas & Dust potentially explosive atmospheres)
Degree Of Protection	IP 66 - 68 (EN60529)
Temperature Classes	-40 C / +80 C with Chloroprene sealing ring. -60 C / +100 C with Silicone sealing ring.

Examination certificated number.....IMQ 11 ATEX 038 X (By IMQ) and IECEx IMQ 13.0006X

Order information

Type	Thread	Material (*)	Plated (**)	Sealing (***)	Ordering Model
EBU01	N (NPT)	B - Brass / X - Stainless Steel A - Aluminium	N (Nickle only for brass)	C (Chloroprene) S (Silicone)	EBU01NBNS

Thread Type (TD mm)	Clamping Range Dia. Min-Max mm	S1+S2+S3 mm	S1+S2 mm	S1 mm	H min mm	L mm	TL mm	SW1 mm	SW2 mm	Model
NPT 1/4"	4.0 - 8.0	4 - 6	6 - 8	-	14.5	30.5	16	22	22	EBU0XSN***
NPT 3/8"	4.0 - 12.0	4 - 6	6 - 9	10 - 12	24	40	16	22	22	EBU01N***
NPT 1/2"	10.0 - 16.0	10 - 12	12 - 14.5	14.5 - 16	29	45	16	28	28	EBU12N***
NPT 3/4"	14.0 - 20.0	14 - 17	17 - 20	-	34	50	16	35	35	EBU23N***
NPT 1"	22.0 - 28.0	22 - 24	24 - 27	28	37	53	16	45	45	EBU34N***
NPT 1 1/4"	26.0 - 34.0	26 - 28	28 - 31	31 - 34	37	55	18	50	50	EBU45N***
NPT 1 1/2"	35.0 - 44.0	35 - 38	38 - 41	41 - 44	45	63	18	55	58	EBU56N***
NPT 2"	46.0 - 56.0	46 - 48	48 - 52	52 - 56	44	62	18	75	80	EBU67N***
NPT 2 1/2"	60.0 - 70.0	60 - 65	65 - 70	-	55	75	20	95	95	EBU78N***
NPT 3"	75.0 - 85.0	75 - 78	78 - 81	81 - 85	57	77	20	105	105	EBU810N***
NPT 4"	85.0 - 95.0	85 - 88	88 - 91	91 - 95	57	77	20	115	115	EBU11N***