



### Technical Data

#### Materials

Lock Nut	Brass Nickle Plated
Attachment Thread	Metric Thread.....EN 60423
	PG Thread.....DIN 40430
	G(PF) Thread.....DIN ISO 228

### Metric Thread Type

Thread Type	H mm	SW mm	D mm	Model
M12x1.5	2.8	15	16.6	BMBL-01
M16x1.5	3.0	19	21.0	BMBL-02
M20x1.5	3.5	24	26.5	BMBL-03
M25x1.5	4.0	30	33.0	BMBL-04
M32x1.5	5.0	36	39.5	BMBL-05
M40x1.5	5.0	46	51.0	BMBL-06
M50x1.5	5.0	60	66.0	BMBL-07
M63x1.5	6.0	70	77.0	BMBL-08
M72x2.0	7.0	77	86.0	BMBL-09
M75x2.0	7.0	80	89.6	BMBL-10
M80x2.0	8.0	90	99.3	BMBL-11
M85x2.0	8.0	95	106.2	BMBL-12
M90x2.0	8.0	100	112.0	BMBL-13

### PG Thread Type

Thread Type	H mm	SW mm	D mm	Model
PG 7	2.8	15	16.6	BSL-01
PG 9	2.8	18	20.0	BSL-02
PG 11	3.0	21	23.5	BSL-03
PG 13.5	3.0	23	25.5	BSL-04
PG 16	3.0	26	29.0	BSL-05
PG 21	3.5	32	35.5	BSL-06
PG 29	4.0	41	45.0	BSL-07
PG 36	5.0	51	56.0	BSL-08
PG 42	5.0	60	66.0	BSL-09
PG 48	5.5	64	70.5	BSL-10

### G(PF) Thread Type

Thread Type	H mm	SW mm	D mm	Model
G 3/8"	5.0	22	24.5	BPFL-01
G 1/2"	5.0	27	30.0	BPFL-02
G 3/4"	5.0	33	36.5	BPFL-03
G 1"	5.0	43	46.5	BPFL-04